4. У. 2 NOTES: UNLESS OTHERWISE SPECIFIED **NEXT ASSY** Ø0.163 [4.13] X 0.625 [15.88] DP. BANANA SOCKET P/N: 9205-HS PERFORMANCE P/N: W-200/COLOR P/N: 9210COLOR HOUSING: MOLDED NYLON. AVAILABLE IN TEN COLORS MAXIMUM CURRENT: 2.5 AMPS 0.070 [1.78] O.D. PVC INSULATION AVAILABLE IN TEN COLORS. FRAME: BRASS. NICKEL PLATED. CONTACT: BeCu OR PHOSPHOR BRONZE. 40µ [1.02µm] MIN GOLD OVER NICKEL PLATED. BODY: BRASS. 40µ [1.02µm] MIN GOLD OVER NICKEL PLATED. MAXIMUM TEMPERATURE: 221°F (105°C) MAXIMUM VOLTAGE: 1000 (300 UL) W.V.D.C. 22AWG 65X40 TINNED COPPER INSULATOR: HEAT SHRINK TUBING 221. BLACK **APPLICATION USED ON** SEE NOTE SEE NOTE MATERIAL FINISH UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES DO NOT SCALE DRAWING · XX + CONTRACT NO. APPROVED BY DRAWN **APPROVALS** *-* 1.100 [27.94] 둤 10/10 DESCRIPTION SIZE | CODE IDENT NO. | DRAWING NO SCALE EZHOOK DIVISION OF TEKTEST INC. DESCRIPTION 08505 9163 REVISIONS 0.750 [19.05] SHEET 1 OF APPROVED