


- NOTES:
- HOUSING MAT'L: LCP, GLASS FILLED, UL94V-0, COLOR-BLACK  
TERMINAL MAT'L: COPPER ALLOY
  - FINISH: SELECT GOLD: 30 MI MIN  
SELECT TIN: 150 / 250 MI  
BOTH OVER NICKEL: 50 MI MIN  
GOLD TO BE SPECIFIED THK IN THIS AREA.
  - PRODUCT SPECIFICATION: PS-45424-001.
  - PACKAGING PER PK-45484-001.
  - THIS MODULE INTERLOCKS WITH ALL STANDARD MOLEX POWER DOCK MODULES
  - DATUM -A- IS THE CONNECTOR MOUNTING SURFACE
  - THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO RoHS DIRECTIVE 2000/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH TIN/LEAD PLATING.
  - PCB HOLE SIZE: SEE PS-45424-001.



PCB LAYOUT: COMPONENT SIDE  
PCB TOLERANCE: ±002/0.05  
PCB THKNESS: .093/2.36 MIN

EC NO: UCP2005-1678	DESCRIPTION
DRWN:KSAMIEC	
CHKD: 2005/11/10	
APPR:APATEL	
2005/11/10	

GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM	
	mm		INCH
4 PLACES	± ---		± ---
3 PLACES	± ---		± ---
2 PLACES	± 0.15		± ---
1 PLACE	± 0.25		± ---
ANGULAR ±1/2°			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			

DRAWN BY	DATE
SCHAFFER	2005/2/8
CHECKED BY	DATE
SAMIEC	2005/2/9
APPROVED BY	DATE
MARGULIS	2005/2/10
MATERIAL NO.	
45524-0001	
SIZE	
A	

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
2:1	METRIC	
TITLE		
POWER DOCK MODULE POWER SOCKET 600V VERT STD CPI		
MOLEX INCORPORATED		
DOCUMENT NO.	SHEET NO.	
SD-45524-001	1 OF 1	
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		